

Down Lite Ceiling Mount

Cat. No. DLCM



Cat. No. DLCMGU



The Down Lite Ceiling Mount is suitable for surface mounting on ceilings using a 3 bolt internal flange system. Water resistant with a 63.5mm diameter mounting base.

This luminaire is machined from a choice of solid aluminium with a UV stable powder coated finish, solid copper or 316 stainless steel with a clear, tempered, flush glass lens and high temperature silicon gaskets

A GU10 version of this luminaire is also available for line voltage lamps.



GU10 Version



Ordering Information

Luminaire Type

DLCM - Down Lite Ceiling Mount

Material/Finish

- BK - Black
- BZ - Bronze
- GN - Green
- STAR - Silver Star
- WH - White
- WB - Birch
- DG - Dark Grey
- OG - Olive Green
- RG - Beige
- PR - Primrose
- COP - Copper
- SS - 316 Stainless Steel

Accessories

- CJK150 - Cable Joint Kit
- LENSSTEPF - Frosted Lens
- GG - Glare Guard
- HCL - Hex Cell Louvre Adaptor
- GU - GU10 Option

Ordering Example: DLCM WH - Down Lite Ceiling Mount in White

LENSSTEPF - Frosted Lens
(Accessories ordered separately)

HUNZA™ PURE
OUTDOOR
LIGHTING

HUNZA FACTORY
130 Felton Mathew Ave
Glen Innes
Auckland 1072
New Zealand

Ph: 64-9-528 9471
Fax: 64-9-528 9361
hunza@hunza.co.nz
www.hunza.co.nz

INTERNATIONAL CONTACTS:
www.hunza.co.nz/contacts.php

Specifications may change without notice.
Manufactured in New Zealand.
© 2011 Hunza Holdings Ltd.

Luminaire Construction

CNC machined from the following metals:
Body: High corrosion resistant low copper 63.5mm (2½") x 10mm (25/64") aluminium. End cap - solid aluminium 63.5mm (2½") rod.

Body: Copper 63.5mm (2½") x 10mm (25/64). End cap - solid copper 63.5mm (2½") rod.

Body: 316 Stainless Steel 63.5mm (2½") x 10mm (25/64) rod. End cap - 316 stainless steel 63.5mm (2½") rod.

Mounting

Via internal flange with three bolts to ceiling.

Features

Lens:

10mm (3/8") clear flush fit shatter resistant glass.

Lifetime Warranty.

Gasket:

Silicone, iron impregnated 220°C (428°F).

Lamp Holder:

GU5.3 & GU10 - 350°C (662°F) ceramic multi contact lamp holder with 250°C (480°F) teflon cables.

Accessories:

Cable Joint Kit (Cat. CJK150)

Not approved for USA/Canada.

Frosted Lens (Cat. LENSSTEPF).

Glare Guard (Cat. GG).

Hex Cell Louvre Adaptor (Cat. HCL).

GU10 Option (Cat. GU).

Standards

IP66  UL1838

Luminaire Weight

12 volt:
 Alum .460kg (1lb)
 Cop 1.200kg (2lb 10oz)
 SS 1.080kg (2lb 6oz)

Power Supply

HUNZA™ Inground or Wall Mount
 Transformer: not included.

USA and Canada:

HUNZA™ Wall Mount: not included
 Approved for internal use.

Luminaire: supplied with

MR16 GU5.3 20 or 35 watt lamp max.
 GU10 - GU10 25 or 35 watt lamp max.

USA and Canada:

MR16 GU5.3 20 or 35 watt lamp max.
 GU10 Halogen - Lamp not supplied

