



## Luminaire Construction

CNC machined from:

### Body:

316 Stainless Steel 63.5mm (2½") x 9mm (11/32"). End cap - solid 316 stainless steel 63.5mm (2½") rod.

### Flange:

90mm x 90mm (3½" x 3½") solid 316 stainless steel bar.

## Mounting

The luminaire is pushed into the canister and is held by two silicone "O" rings: Canss, FLcan, FLucan are cast into concrete, brick, concrete block, etc.

Dkcan: Mounted into wooden decks, wooden frames, etc.

## Features

### Lens:

3mm (1/8") clear tempered shatter resistant glass.

Lifetime Warranty.

### Gasket:

Silicone, iron impregnated 220°C (428°F).

### Lamp Holders:

GU5.3 & GU10 - 350°C (662°F) ceramic multi contact lamp holder with 250°C (480°F) teflon cables.

### Accessories:

Cable Joint Kit (Cat. CJK150)

Not approved for USA/Canada.

Deck Canister (Cat. Dkcan).

Frosted Lens (Cat. LENSSTEPF).

GU10 Option (Cat. GU).

Hex Cell Louvre Adaptor (Cat. HCL)

(Note: Supplied as standard for USA/Canada).

316 Stainless Canister for use in lime stone etc. (Cat. Canss).

## Standards

EN60598

IP66/IP68



UL1838

## Luminaire Weight

SS 1.175kg (2lb 9oz)

SS 1.810kg (3lb 15oz)

## Power Supply

HUNZA™ Inground or Wall Mount Transformer: not included.

## USA and Canada:

HUNZA™ Wall Mount Transformer: not included.

## Luminaire: supplied with


MR16 GU5.3 - 20 watt lamp max.

GU10 - GU10 25 or 35 watt lamp max.

## USA and Canada:

MR16 GU5.3 20 watt lamp max. GU10 Halogen - Lamp not supplied

MR16 ESX GU5.3  
12 volt 20 watt 10°




4000 Lux @ ∅ 200mm (8")

1000 Lux @ ∅ 400mm (16")

444 Lux @ ∅ 600mm (24")

MR16 BAB GU5.3  
12 volt 20 watt 38°




700 Lux @ ∅ 650mm (26")

175 Lux @ ∅ 1300mm (51")

78 Lux @ ∅ 1950mm (76")

MR16 GU5.3  
12 volt 20 watt 60°



450 Lux @ ∅ 1154mm (45")

112 Lux @ ∅ 2308mm (91")

50 Lux @ ∅ 3462mm (136")

These diagrams refer to the Spot Lite Flange (E) only.

**HUNZA**™ PURE OUTDOOR LIGHTING

HUNZA FACTORY  
130 Felton Mathew Ave  
Glen Innes  
Auckland 1072  
New Zealand

Ph: 64-9-528 9471  
Fax: 64-9-528 9361  
hunza@hunza.co.nz  
www.hunza.co.nz

INTERNATIONAL CONTACTS:  
www.hunza.co.nz/contacts.php

Specifications may change without notice.  
Manufactured in New Zealand.  
© 2011 Hunza Holdings Ltd.

Ver 1.4