

Wall Spot ULTRA 35

PROJECT: _____

TYPE: _____


SOURCE: _____

NOTES: _____

SPECIFICATIONS



LED Chip	Cree CXA 1830 field replaceable LED board
Luminaire Output	2700 Lumens @ 700mA (26 watts) , Delivered from Luminaire with unobstructed beam.
Lumens Per Watt	100 Lumens minimum @ 26 watts, Delivered from Luminaire with unobstructed beam
CRI (3000K)	80 Standard, 90+ Optional
Colour Temperatures	2700K, 3000K, 4000K
Beam Angles	13, 20, 25, 34
Ingress Protection	IP66
Warranty	Electronics = 5 years Body Aluminium = 5 years
Standards	BS/EN 60598.2.2 cUL 1598 PENDING CE



PRODUCT CONFIGURATION

Please fill in appropriate codes into boxes provided

Cat. No. WS/U35

Luminaire	Power	Material/ Finish	Beam	Colour	Accessories
WS/U35					
SR SERIES REMOTE R RETRO, 120-277vac INPUT		ALUMINIUM EBK BLACK EBZ BRONZE EOGR OLIVE GREEN EWH WHITE EWB WHITE BIRCH EDG DARK GREY ESTAR SILVER STAR ECT CORTEN	13 13° 20 20° 25 25° 34 34°	2 2700K 3 3000K 4 4000K 39 3000K, 90+ CRI	ULT35HC HEX CELL LOUVRE ULT35SNT SNOOT ULT35GG GLARE GUARD WP/U35 WALL PLATE LARGE CJK CABLE JOINT KIT

SERIES REMOTE:
Constant current driver (included)
Fixture require 37vdc @ 700mA maximum

**RETRO
110-277vac DRIVER:**
Constant current driver (included)
Input: 120,240,277 volts
Output: 30 watts total
37vdc @ 700mA
0-10 volt dimming

ADDITIONAL COMMENTS:

LUMINAIRE CONSTRUCTION

CNC machined from one of the following metals:

Body - solid high corrosion resistant 101mm (4") aluminium rod.
 Base - high corrosion resistant 101mm (4") aluminium Rod.
 Finished with chromate substrate, Epoxy layer and a UV resistant polyester powder coat colour.
 Fixings and Mechanism - made from 316 Stainless Steel

Colours:

Black, Bronze, Silver Star, White, Birch, Olive Green, Dark Grey, Corten.

Step Lens:

12mm (1/2") Extra clear, low iron, shatter resistant glass.
 Lifetime warranty

Gaskets:

Silicone, iron impregnated 220°C (428°F)

Cable:

Water resistant rubber

Adjustability:

The fully adjustable head allows 360 degrees rotation and 0-120 degrees elevation and can then be fixed in place using the inbuilt locking mechanism.


Mounting:

The mounting plate is fixed to the surface using three stainless screws. The luminaire is then fixed to the mounting plate

Luminaire Weight:

4kg (9 lbs)


ACCESSORIES



BEAM ANGLES



High efficiency Reflectors. Field replaceable

IES files available for download: www.hunzalighting.com/download.php



WIRING GUIDE

available for download: www.hunzalighting.com/download.php



Diagrams are a guide only, wire colours and polarity may change depending on fixture and country