



Wall Mount Transformer

Cat. No. WM100, WM200, WM300.



6 5/16" |
160mm



10" |
245mm

2 7/16" |
62mm

The HUNZA™ Wall Mount Series Transformers have a black glass reinforced UV stabilised nylon case for durability which also maintains a low operating temperature. The transformer is encapsulated into the case for protection against weather and irrigation systems. The transformers are available in 100, 200, 300 watt output.

Dimmable by low voltage leading or trailing edge dimmers, providing superior energy efficiency.

Ordering Information

Transformer

WM100 - 100watt
WM200 - 200watt
WM300 - 300watt

Case Material

UV Stable Glass reinforced Nylon 66



Ordering Example: WM300 - Wall Mount Transformer 300 watt output.

HUNZA™ PURE
OUTDOOR
LIGHTING

HUNZA FACTORY
130 Felton Mathew Ave
Glen Innes
Auckland 1072
New Zealand

Ph: 64-9-528 9471
Fax: 64-9-528 9361
hunza@hunza.co.nz
www.hunza.co.nz

INTERNATIONAL CONTACTS:
www.hunza.co.nz/contacts.php

Specifications may change without notice.
Manufactured in New Zealand.
© 2010 Hunza Holdings Ltd.

Ver 1.4

Transformer Construction

Case:

Glass filled UV stabilised Nylon 66.
With rear heat reduction system for cool running.

Transformer:

Encapsulated Toroidal, Class E insulation, dual primary voltage (120 /240 volt) with multi tap (12, 13, 14 volts) secondary fused with ceramic link.

Transformer: 100, 200, 300 watt.

Mounting

The case is screwed directly to a flat mounting surface.

Features

Terminal Block Size:

Primary 16mm (6AWG).

Secondary 16mm (6AWG).

Voltages:

Primary
120 volt 60Hz or 240 volt 50Hz.

Secondary
Multi Tap 12, 13, 14 volts.

Wattages:

100 watt:
200 watt:
300 watt:

Conduit Entry:

Primary - 25mm (1")

Secondary - 32mm (1¼")

Protection:

Fused secondary with ceramic fuse for short circuit protection.

Standards

IP66

AS/NZS 61046



UL1838

Transformer Weight

100 watt: 1.600kg (3lb 8oz)
200 watt: 2.065kg (4lb 8oz)
300 watt: 2.600kg (5lb 11oz)