

**HUNZA PURE LED SPECIFICATION CHART**

Apr-18

FITTING	LED CHIP	LIGHT OUTPUT (LUMENS)				WATTAGE			
		350MA	700MA	1050MA	2050MA	350MA	700MA	1050MA	2050MA
ARCH BOLLARD	CXA	-	3000	-	-	-	26	-	-
BOLLARD 300 & 700	XHP	-	300	510	-	-	4	6	-
BOLLARD MINI	XPG3	65	120	-	-	1	2	-	-
BORDER LITES	XPG3	65	120	(per head)	-	1	2	(per head)	-
CUBE LITES	XPG3	65	120	200	-	1	2	3	-
DOWN LITE	XHP	-	420	600	-	-	4	6	-
DRIVEWAY LITE	XHP	-	420	600	-	-	4	6	-
EAVE LITE	XHP	-	420	600	-	-	4	6	-
EAVE/T3 (TILTING)	XPG3	-	120	200	-	-	2	3	-
EAVE/T6 (TILTING)	XHP	-	420	600	-	-	4	6	-
EURO FIXTURES (ALL)	XHP	-	420	-	-	-	4	-	-
FERN LITE	XHP	-	420	600	-	-	4	6	-
FLOOR LITES (ALL)	XHP	-	420	600	-	-	4	6	-
HANGING LITE	XHP	-	420	600	-	-	4	6	-
HIGH POWER RANGE	XHP	-	-	-	1000	-	-	-	12
LAWN LITE	XHP	-	420	600	-	-	4	6	-
MOUSE LITES	XPG3	65	120	-	-	1	2	-	-
NPS SPOT	XHP	-	420	600	-	-	4	6	-
PAGODA LITE	XHP	-	420	-	-	-	4	-	-
PATH LITES (ALL)	XHP	-	420	600	-	-	4	6	-
PILLAR LITE	XHP X 2	-	420	(per side)	-	-	8	-	-
POLE SPOT	XHP	-	420	600	-	-	4	6	-
POND LITES	XHP	-	420	600	-	-	4	6	-
POOL LITE	XHP	-	420	600	-	-	4	6	-
SIGN LITES	XHP	-	420	600	-	-	4	6	-
SINGLE POLE LITE	XHP	-	420	600	-	-	4	6	-
SPIKE SPOT	XHP	-	420	600	-	-	4	6	-
ULTRA	CXA	-	-	5000 (@ 1400MA)	-	-	-	62.5 (@ 1400MA)	-
STEP LITES (ALL)	XHP	-	420	600	-	-	4	6	-
TIER LITE	XHP	-	420	600	-	-	4	6	-
TWIG LITE	XPG3	65	120	-	-	1	2	-	-
TWIN BAR LITE	XHP X 2	-	420	600	(per head)	-	8	12	-
TWIN POLE LITE	XHP X 2	-	420	600	(per head)	-	8	12	-
WALKWAY LITE	XPG3	65	120	-	-	1	2	-	-
WASHER	CXA	-	-	600	-	-	9	-	-
WALL SPOTS	XHP	-	420	600	(per head)	-	4	6	(per head)